

Manual

Queensland Guide to Temporary Traffic Management Part 8: Processes and Procedures

July 2024



Copyright

© The State of Queensland (Department of Transport and Main Roads) 2024.

Licence



This work is licensed by the State of Queensland (Department of Transport and Main Roads) under a Creative Commons Attribution (CC BY) 4.0 International licence.

CC BY licence summary statement

In essence, you are free to copy, communicate and adapt this work, as long as you attribute the work to the State of Queensland (Department of Transport and Main Roads). To view a copy of this licence, visit: <u>https://creativecommons.org/licenses/by/4.0/</u>

Translating and interpreting assistance



The Queensland Government is committed to providing accessible services to Queenslanders from all cultural and linguistic backgrounds. If you have difficulty understanding this publication and need a translator, please call the Translating and Interpreting Service (TIS National) on 13 14 50 and ask them to telephone the Queensland Department of Transport and Main Roads on 13 74 68.

Disclaimer

While every care has been taken in preparing this publication, the State of Queensland accepts no responsibility for decisions or actions taken as a result of any data, information, statement or advice, expressed or implied, contained within. To the best of our knowledge, the content was correct at the time of publishing.

Feedback

Please send your feedback regarding this document to: tmr.techdocs@tmr.qld.gov.au

About this document

This document supplements the Austroads *Guide to Temporary Traffic Management Part 8: Processes and Procedures*, which provides guidance to road authorities, road infrastructure managers, any party conducting works on, or near a road, and all persons involved in planning, designing, implementing, managing and completing temporary traffic management works. It details the processes and procedures relating to jurisdictional management of temporary traffic management at roadworks. The information included covers: categories of temporary traffic management; powers, roles and responsibilities; training; and standard forms and descriptions.

How to use this document

This document is designed to be read and applied together with the Austroads *Guide to Temporary Traffic Management Part 8: Processes and Procedures* (AGTTM08-19 Edition 1.0). You must have access to the Guide to understand what applies in Queensland.


This document:

- sets out how AGTTM08-19 applies in Queensland
- has precedence over AGTTM08-19 when applied in Queensland
- has the same section and clause numbering and headings as AGTTM08-19.

The following table summarises the relationship between AGTTM08-19 and this document:

Applicability	Meaning	
Accepted	The Guide section or clause is accepted.	
Accepted, with amendments	Part or all of the section or clause has been accepted with additions, deletions or differences.	
New	There is no equivalent section or clause in the Guide.	
Not accepted	The Guide section or clause is not accepted.	

A summary of the documents relevant to TTM practice in Queensland, and their links, is provided following:



References

The following references apply when reading AGTTM08-19.

Reference to	Means
AGTTM08-19	Austroads <i>Guide to Temporary Traffic Management Part 8: Processes</i> <i>and Procedures</i> , as amended by this document: for example, a reference to AGTTM08-19 means you must refer to the <i>Queensland</i> <i>Guide to Temporary Traffic Management</i> (QGTTM) Part 8.
	Throughout AGTTM08-19, references are made to other parts of the Guide (for example, when reading Part 8 you may be referred to Part 3 for further information.) In this case, you must refer to the equivalent Part within the QGTTM. Check the applicability of the equivalent Part in the QGTTM before referring to the referenced Austroads Guide Part.
AGTTM	Austroads Guide to Temporary Traffic Management
AS 1742	Australian Standard AS 1742 Manual of Uniform Traffic Control Devices
Queensland (Q) series / Traffic Control (TC) signs	MUTCD (Q) series and TC signs.
Queensland MUTCD	Queensland Manual of Uniform Traffic Control Devices which supplements AS 1742.

Section		Description	Applicability
1 Introduct		ion	
	1.1	Purpose	Accepted
	1.2	Structure of AGTTM	Accepted
	1.3	Scope of Part 8	Accepted
	1.4	Application of Part 8 to New Zealand	Accepted
	1.5	Acronyms	Accepted
	1.6	Definitions	Accepted
2	Road cat	egories for temporary traffic management	
	2.1	General	Accepted
	2.2	Default TTM road categories	Accepted, with amendments
	2.3	Project specific amendments to TTM road categories	Accepted
	2.4	Road categories map for Queensland	New
3	Process	for TGS selection	
	3.1	General	Accepted
	3.2	Generic TGS	Accepted, with amendments
	3.3	Site suitable TGS	Accepted, with amendments
	3.4	Site specific TGS	Accepted
	3.5	TGS type selection	Accepted, with amendments
4	TTM app	M approval activities	
5	Powers, roles and responsibilities		
	5.1	Legislative context	Accepted
	5.2	Statutory health and safety responsibilities – duty of care	Accepted
	5.3	Application of the Parts of AGTTM	Accepted
	5.4	Roles and responsibilities	Accepted, with amendments
	5.5	Roles and responsibilities for special applications	Accepted
	5.5.1	Road safety barrier systems	Accepted with amendments
	5.5.2	Austroads Safety Hardware Training and Accreditation Scheme (ASHTAS)	New
	5.6	Supervising a Traffic Controller (TC) in training	New
6	TTM train	ning framework	Accepted, with amendments
	6.1	Application of TTM training framework	Accepted, with amendments
	6.2	Training roles	Accepted, with amendments
	6.3	Training by road category	Accepted, with amendments
	6.4	Training – general	Accepted, with amendments

Relationship table (harmonised to AGTTM08-19 Edition 1.0)

Section		Description	Applicability
	6.4.1 Competencies		Accepted, with amendments
6.4.2		Assessment	Accepted, with amendments
6.5		Traffic controller	Accepted, with amendments
	6.5.1	Training by road category	Accepted, with amendments
	6.5.2	Competencies	Accepted, with amendments
	6.5.3	Progression between categories	Accepted, with amendments
	6.6	Traffic management implementer	Accepted, with amendments
	6.6.1	Training by road category	Accepted, with amendments
	6.6.2	Competencies	Accepted, with amendments
	6.6.3	Progression between categories	Accepted, with amendments
	6.7	Traffic management designer	Accepted, with amendments
	6.7.1	Training by road category	Accepted, with amendments
	6.7.2	Competencies	Accepted, with amendments
	6.7.3	Progression between categories	Accepted, with amendments
	6.8	Practitioner and non-practitioner status	Accepted, with amendments
	6.9	Maintenance of qualification currency	Accepted, with amendments
7	Standard	l forms	
8	Model co	entract specification	
Appendie	ces		
Α	TTM roles	s – additional tasks and activities	Accepted, with amendments
		Table A1: Engineer	Accepted
		Table A2: Project manager	Accepted
		Table A3: Traffic management designer	Accepted
		Table A4: Traffic controller	Accepted
		Table A5: Traffic management implementer	Accepted with amendments
		Table A6: Principal contractor	Accepted
		Table A7: Traffic management worker	Accepted, with amendments
B Standard forms – examples		forms – examples	
	B.1	Form B.1 – TMP suitability checklist	Accepted
	B.2	Form B2 – Traffic management for roadworks operational check / onsite pre-opening inspection – checklist	Accepted
	В.З	Form B3 – Worksite traffic management – hierarchy of safety controls – checklists	Accepted
	B.3.1	Using the checklist	Accepted
	B.3.2	Form B3 – CHECKLIST PART A – Traffic controls assessment	Accepted
	B.3.3	Form B3 – CHECKLIST Part B – Justification for control selection	Accepted

Section		Description	Applicability
	B.3.4 Form B3 – CHECKLIST Part C – Additional site-specific safety hazard / risk factors		Accepted
	B.4	Form B4 – TMP daily traffic management diary	Accepted
	B.5	Form B.5 – Traffic Management Plan (TMP) – long form	Accepted
	B.6	Form B.6 – Design exception	Accepted
	B.7	Form B.7 – Example of site condition rating (SCR) form – compliance inspection	Accepted
	B.8	Form B.8 – Example of site condition rating (SCR) form – compliance inspection – short form	Accepted
	B.8.1	Examples of ratings (short audit)	Accepted
	B.9	Form B.9 – Example of notice of non-conformance	Accepted
	B.10	Form B.10 – Example of notification of road closure / lane closure	Accepted
	B.11	Form B.11 – Report on incident at roadworks site	Accepted
	B.12	Form B.12 – Newspaper advertisement standard	Accepted
С	Sample temporary traffic management specification template local government roads		
	C.1	Specification	Accepted
	C.1.1	Location and description of work	Accepted
	C.1.2	Extent of work	Accepted
	C.1.3	Setting out the works	Accepted
	C.1.4	Scope of work	Accepted
	C.1.5	Traffic guidance scheme (TGS)	Accepted
	C.1.6	Record keeping and audit requirements	Accepted
	C.1.7	Emergency and public transport vehicles	Accepted
	C.1.8	Numbers of traffic controllers	Accepted
	C.1.9	Traffic management plans	Accepted
	C.1.10	Arrangement of traffic control devices	Accepted
	C.1.11	Adequate traffic control devices	Accepted
	C.1.12	Opening completed work	Accepted
	C.1.13	Use of 40 km/h speed zoning	Accepted
	C.1.14	Flashing arrow signs	Accepted
	C.1.15	Message boards	Accepted
	C.1.16	Water filled delineators and crash barriers	Accepted
	C.1.17	Barrier boards	Accepted

Section		Description	Applicability
C.1.18		Cones and bollards	Accepted
C.1.19 C.1.20		Traffic signals	Accepted
		Devices to be safely supported	Accepted
C.1.21		Permanent traffic signals	Accepted
	C.1.22	Alternative duties	Accepted
	C.1.23	Control of worksites	Accepted
	C.1.24	Compliance with standards, handbooks and guides	Accepted
	C.1.25	Safety	Accepted
D	Sample te	emporary traffic management specification State / Territory Government roads	
	D.1	Scope	Accepted
	D.1.1	General	Accepted
	D.1.2	Traffic management plan	Accepted
	D.2	Temporary traffic management (TTM) personnel	Accepted
	D.2.1	Authority to direct traffic	Accepted
	D.2.2	Traffic management implementer	Accepted
D.3		Planning and design	Accepted
	D.3.1	General	Accepted
D.3.2		Hazard identification, risk assessment and control	Accepted
	D.3.3	Objective and targets	Accepted
	D.3.4	Temporary speed zoning	Accepted
	D.3.5	Least possible disruption	Accepted
	D.3.6	Maintain access to adjoining properties and side roads	Accepted
	D.4	Road occupancy licence	Accepted
	D.4.1	Road occupancy licence application	Accepted
	D.4.2	Road occupancy fees	Accepted
	D.4.3	Licence conditions	Accepted
	D.5	Traffic management plan (TMP)	Accepted
	D.5.1	Plan submission	Accepted
	D.5.2	Required elements	Accepted
	D.5.3	Plan preparation	Accepted
	D.5.4	Contractor's responsibility	Accepted
	D.6	Traffic staging plans	Accepted
	D.6.1	General	Accepted
	D.6.2	Required details	Accepted

Section		Description	Applicability
	D.6.3	Safety barriers	Accepted
	D.7	Traffic Guidance Schemes	Accepted
	D.7.1	Plan submission	Accepted
	D.7.2	Generic traffic guidance schemes	Accepted
	D.7.3	Project specific traffic guidance schemes	Accepted
	D.7.4	Required details	Accepted
	D.8	Vehicle movement plans and pedestrian movement plans	Accepted
	D.8.1	Vehicle movement plans	Accepted
	D.8.2	Pedestrian movement plans	Accepted
	D.9	Road safety audit of TMPs	Accepted
	D.10	Traffic management risk assessment workshop	Accepted
	D.10.1	General	Accepted
	D.10.2	Content of workshop	Accepted
	D.10.3	Participants	Accepted
	D.10.4	Close out identified risk issues	Accepted
	D.11	Temporary roadways and detours	Accepted
	D.11.1	Construction of temporary roadways and detours	Accepted
	D.11.2	Opening temporary roadways and detours to traffic	Accepted
	D.11.3	Road safety audit of temporary roadways or detours	Accepted
	D.11.4	Removal of temporary roadways and detours	Accepted
	D.12	Traffic control devices	Accepted
	D.12.1	Safety barriers	Accepted
	D.12.2	Pavement markings and signs	Accepted
	D.12.3	Portable variable message signs	Accepted
	D.12.4	Radar activated speed signs	Accepted
	D.12.5	Temporary traffic signals	Accepted
	D.13	Monitoring of traffic control measures	Accepted
	D.13.1	Communication	Accepted
	D.13.2	Emergency preparedness and response	Accepted
	D.13.3	Incident investigation, corrective and preventative action	Accepted
	D.14	Side-tracks and detours	Accepted
	D.15	Opening to traffic upon completion	Accepted

Contents

Abou	t this document	.i
How	o use this document	.i
Refe	ences	ii
Rela	onship table (harmonised to AGTTM08-19 Edition 1.0)i	ii
2	Road categories for temporary traffic management	1
2.2	Default TTM road categories	1
2.4	ITM road categories map for Queensland	2
3	Process for TGS selection	3
3.2	Generic TGS	3
3.3	Site suitable TGS	3
3.5	ΓGS type selection	3
5	Powers, roles and responsibilities	4
5.4	Roles and responsibilities	4
5.5	Roles and responsibilities for special applications	4
	5.5.1Road safety barrier systems5.5.2Austroads Safety Hardware Training and Accreditation Scheme (ASHTAS)	
5.6	Supervising a Traffic Controller (TC) in training	6
6	ITM training framework	6
Арре	ndix A TTM Roles – Additional tasks and activities	7

Tables

Table 5.14 – Temporary road safety barriers	4
Table A7: Traffic management worker	7

2 Road categories for temporary traffic management

2.2 Default TTM road categories

Difference

Replace:

Category 1 (most urban streets and lower volume rural roads). The characteristics of category 1 roads are defined by the following parameters:

- Posted speed and AADT of:
 - any speed limit with less than 3,000 vehicles per day AADT
 - a speed limit of less than 60 km/h and traffic volumes between 3,000 and 10,000 vehicles per day AADT

with:

Category 1 (most urban streets and lower-volume rural roads) includes single carriageway roads with a posted speed limit of:

- less than 60 km/h where the Annual Average Daily Traffic (AADT) is less than 10,000, or
- 110 km/h or less where the AADT is less than 3000.

Difference

Replace:

Category 2 (high volume roads). The characteristics of category 2 roads are defined by the following parameters:

- Posted speed and AADT of:
 - a speed limit greater than, or equal to 60 km/h and traffic volume greater than, or equal to 3,000 vehicles per day AADT
 - any speed limit with traffic volumes greater than, or equal to 10,000 vehicles per day AADT
- Signalised intersections
- The characteristics of these roads are recognised as:
 - multilane or divided roads
 - high speed highways.

with:

Category 2 (high volume roads) comprises anything not in Category 1 or 3, and includes roads with:

- any signalised intersection
- multiple lanes in a single direction (excluding overtaking and turn lanes)

Difference

Replace:

Category 3 (expressways = high-volume & high-speed roads). The characteristics of category 3 roads are defined by the following parameters:

- These are high-volume expressways, or high-volume / high-speed multi-lane expressways with a divided carriageway
- Any expressway and any associated on-ramp or off-ramps
- Grade separated road with speed limit greater than, or equal to 90 km/h. Traffic volumes are generally greater than 20,000 VPD but can be lower

with:

Category 3 (expressways = high-volume & high-speed roads) includes:

- Expressways (that is, freeway, motorway or tunnel-type roads) and associated on-ramps or off-ramps, or
- grade-separated roads with:
 - posted speed limit greater than or equal to 90 km/h, and
 - AADT greater than 20,000.

2.4 TTM road categories map for Queensland

<u>New</u>

TTM road categories for roads across Queensland have been determined and are available on <u>Queensland Globe</u>. This map only shows Category 2 or 3 roads, with all other roads being Category 1. The *TTM Road Categories* map layer on Queensland Globe is accessible by following these steps:

- Click on 'Layers'.
- Click on 'Add Layers'.
- Scroll down to the 'Transportation' category and expand the layer list using the dropdown arrow.
- Select the 'Temporary traffic management road categories' layer by checking the tick box.

Please note that:

- A list of Local Government Authorities (LGAs) and their Queensland Globe map status is available on the <u>QGTTM</u> webpage. If no roads are displayed for the LGA in Queensland Globe, please check the LGA map status document and, if 'not included', contact the LGA directly, noting that only Category 2 and 3 roads are displayed on Queensland Globe. Additional road category information will be added to Queensland Globe by Transport and Main Roads for LGAs as this information becomes available.
- The road category layer is only visible at certain zoom levels, so navigate to your area of interest and zoom in to view the current *TTM Road Categories*.

• To enhance the visibility of the TTM category layer, deselect other road network layers and use the 'Queensland basemap grey' layer in place of the imagery layer. You can toggle them on and off as required.

If you are new to Queensland Globe, there is a range of tutorial videos available under the 'Help' section.

The TTM road categories map on the Queensland Globe will be maintained and updated by Transport and Main Roads periodically. Please email <u>TrafficEngineering.Support@tmr.qld.gov.au</u> with any requested changes.

3 Process for TGS selection

3.2 Generic TGS

Addition

In addition, a generic TGS developed specifically for and in accordance with QGTTM Part 5 *Short-Term Low-Impact Worksites* may be selected by a person with *Working in Proximity to Traffic Awareness – Part 2* competency, excluding works involving grading, protection by a shadow vehicle with (or without) a truck-mounted attenuator, or QGTTM Part 5 Sections 4.1, 4.4 and 4.5.

3.3 Site suitable TGS

<u>Addition</u>

In addition, a generic TGS developed specifically for and in accordance with QGTTM Part 5 *Short-Term Low-Impact Worksites* may be confirmed as site suitable and signed off by a person with *Working in Proximity to Traffic Awareness – Part 2* competency, excluding works involving grading, protection by a shadow vehicle with (or without) a truck-mounted attenuator, or QGTTM Part 5 Sections 4.1, 4.4 and 4.5.

3.5 TGS type selection

Difference

Replace Note 3 to Figure 3.1:

(3) 'Modifications' are changes or additions to the Generic TGS which require design and approval by a TMD-qualified person.

with:

(3) 'Modifications' are changes or additions to the generic TGS which require design and approval by a TMD-qualified person or where mandatory conditions cannot be complied with and require design and approval from an RPEQ with TMD competency.

Addition

Add the following additional note to Figure 3.1

(5) For a generic TGS developed specifically for and in accordance with QGTTM Part 5 Short-Term Low-Impact Worksites, the items in the flow chart assigned to a TMI may be performed by a person with Working in Proximity to Traffic Awareness – Part 2 competency, excluding works involving grading, protection by a shadow vehicle with (or without) a truck-mounted attenuator, or QGTTM Part 5 Sections 4.1, 4.4 and 4.5.

5 Powers, roles and responsibilities

5.4 Roles and responsibilities

Difference

Delete the following RIM responsibility from Table 5.3:

• authorising Design Exceptions (DESs).

5.5 Roles and responsibilities for special applications

5.5.1 Road safety barrier systems

Difference

Replace Table 5.14 with the following:

Table 5.14 – Temporary road safety barriers

Task	Description	Competent Person	
Determine the need for a temporary road safety barrier	Works require the use of a temporary road safety barrier system due to worker or road user safety	TMD	
Selection of temporary road safety barrier system	Compare various temporary road safety barrier systems and select the most suitable for the specific site	TMD who has completed specific training and is deemed competent in the design of	
Design of temporary road safety barrier in complete accordance with approved guidelines	Complete the design of the barrier system including (but not limited to) the location / length of need / fixing / deflection limits and end treatment requirements	temporary road safety barrier systems or Specialist temporary road safety barrier designer in consultation with the TMD or Engineer with temporary road safety barrier design expertise	
Design of temporary road safety barrier which is outside the scope of the manufacturer's supplied manuals / guidelines	Engineer certification is required for all areas of the design and installation which are outside the scope of (or not included in) the manufacturer's supplied manuals / guidelines	Engineer with temporary road safety barrier design expertise	
Install a temporary road safety barrier system	Install the temporary road safety barrier as nominated on the TGS, in accordance with the manufacturer's supplied manuals / guidelines and instructions from the competent person	TMI competent with the installation of the selected temporary road safety barrier or Specialist temporary road safety barrier installer	
Certification of manufacturer's supplied manuals / guidelines	Temporary road safety barrier suppliers must ensure all manufacturer's supplied manuals / guidelines are appropriately certified by an Engineer	Engineer or equivalent with temporary road safety barrier design expertise	

Addition

Add the following commentary to Table 5.14:

The <u>Road Safety Barrier Awareness</u> course Transport and Main Roads offers is an awareness course which does not issue attendees with a certificate or competency in road safety barrier design. While the Transport and Main Roads Road Safety Barrier Awareness course will provide some knowledge on temporary road safety barriers, the 'completed specific training and is deemed competent in the design of temporary road safety barrier systems' requirement in Table 5.14 would require more than just the completion of the Transport and Main Roads Road Safety Barrier Safety Barrier Awareness course.

The following is provided to expand on the requirements in Table 5.14:

- A TMD may determine the need for a temporary road safety barrier.
- A TMD who has completed specific training and is deemed competent in the design of temporary road safety barrier systems may, based on site parameters and manufacturer specifications, select or recommend a particular temporary road safety barrier system which will suit the works and the roadworks site.
- A TMD may use the manufacturer's supplied manuals / guidelines to design the temporary road safety barrier system; however, the TMD would need some expertise in designing temporary road safety barriers and have completed specific training and is deemed competent in the design of temporary road safety barriers systems including, at a minimum, training in designing the selected temporary road safety barrier system from the manufacturer's supplied manuals / guidelines.
- If the temporary road safety barrier design is outside the manufacturer's supplied manuals / guidelines, then this will require the design to be completed and signed off by an RPEQ with temporary road safety barrier design expertise.

Only road safety barrier systems included on the current list of products in the Transport and Main Roads <u>Accepted Road Safety Barrier Systems and Devices</u> document shall be used at roadwork sites in Queensland.

5.5.2 Austroads Safety Hardware Training and Accreditation Scheme (ASHTAS)

<u>New</u>

In addition to the requirements above, ultimately the Austroads Safety Hardware Training and Accreditation Scheme (ASHTAS) will, over time, offer courses for Safety Barrier Operative (Entry Level), Installers (Permanent and Temporary Safety Barriers), Designers (Permanent and Temporary Safety Barriers), and more.

Currently, the Safety Barrier Operative (Entry Level) course has been created and is available. Austroads is in the final stages of completing the Installer course for permanent barriers, which will be released in the near future. However, Austroads hasn't established a specific date or timeframe for the Installer - Temporary Barrier course yet. The Designer - Temporary Barrier course is further away in development.

Once the Installer - Temporary Barrier and Designer - Temporary Barrier courses are available, they will be significantly more effective than the general awareness courses currently available. These ASHTAS courses will have direct input from each product manufacturer and will provide practical training.

From 1 July 2024, TMR will require all individuals involved in the design, installation, and maintenance of temporary roadside safety barriers to obtain an ASHTAS license. The required licence will be based on the training developed and available at that time. For more information, visit https://www.tmr.qld.gov.au/business-industry/technical-standards-publications/ASHTAS.

5.6 Supervising a Traffic Controller (TC) in training

<u>New</u>

When a TC in training is acquiring experience to satisfy the practical assessment component of their training, they shall be directly supervised by a TC deemed competent at the relevant TTM Category.

For further information regarding the supervision of a TC in training see QGTTM Part 7.

6 TTM training framework

Difference

Replace Sections 6.1 through to 6.9 with the following:

Competent persons (Clause 1.3.2 of <u>Queensland MUTCD</u> Part 3) in Queensland shall undertake prescribed training developed by Transport and Main Roads and delivered by RTOs licenced by the department to deliver this training. Information on the prescribed training courses is provided in Clause 1.7 of Queensland MUTCD Part 3.

Accredited persons may work on any road category.

Appendix A TTM Roles – Additional tasks and activities

Addition

The tables following outline the various TTM duties in relation to the selection, design, implementation, monitoring or modification of a Traffic Management Plan (TMP) or a Traffic Guidance Scheme (TGS) which may be performed based on the competent person definitions in Clause 1.3.2 Queensland MUTCD Part 3.

A competent person shall only undertake activities relevant to their temporary traffic management role.

A person holding multiple competencies (qualifications) may apply all of the relevant sections for those competencies (or qualifications) as identified in the table following. If an activity is not listed for a given competency, then that activity cannot be conducted under that competency.

Difference

In Table A5 replace:

The person under instruction should have the Working Safely Near Traffic training unit competency.

with:

The person under instruction must be a Working in Proximity to Traffic Awareness Part 1 Competent Person or a Queensland accredited traffic controller.

Difference

Replace Table A7 with the following:

Table A7	: Traffic	management	worker
----------	-----------	------------	--------

Competent person – Working in Proximity to Traffic Awareness – Part 1				
Task – Implementation				
Activity	Additional Information			
 Install or remove signs under direct supervision and instruction by a <i>Working in Proximity to Traffic Awareness – Part 2</i> Competent Person, where those devices are part of a work method practice or TGS developed in accordance with the short-term, low-impact works in QGTTM Part 5, excluding works involving: a) grading, or b) protection by a shadow vehicle with (or without) a truck-mounted attenuator, or c) the use of sections 4.1, 4.4 or 4.5. 	intervene if required.			
Install or remove signs and other devices included o a TGS under direct supervision and instruction by a TMI Competent Person	n Direct supervision requires the supervising TMI to hold the Traffic Management Implement competency at the appropriate road category, and be present (in close proximity) and able to intervene if required			
Cover or uncover signs	Generally, at the end or start of a shift. Instruction must be included on the TGS that the signs can be covered or uncovered and at what times or under what conditions.			
Record Keeping	Daily record of installed traffic management signs and devices in accordance with <u>QGTTM</u> Part 6 Section 7.			

Task – Implementation	
Activity	Additional Information
Modify the TGS on site in response to an emergency event	In accordance with QGTTM Part 10 Section 5.2 <i>Initial Response</i> only.
Competent person – Working in Proximity to Traffic	Awareness – Part 2
All of the Tasks and Activities for a <i>Working in Proximit</i> addition to the following.	y to Traffic Awareness Part 1 Competent Person, in
Task – Selection and Implementation	
Activity	Additional information
Select, design and implement a work method practice (including the installation or removal of signs) in accordance with the short-term low-impact works in QGTTM Part 5, excluding works involving: a) grading, or b) protection by a shadow vehicle with (or without) a truck-mounted attenuator, or c) the use of sections 4.1, 4.4 or 4.5	Develop a simple sketch as part of the on-site record keeping requirements for short-term low-impact works in accordance with QGTTM Part 5.
	Signs applicable for installation or removal by a <i>Working in Proximity to Traffic Awareness – Part 2</i> Competent Person are only those required for compliance with the relevant sections of the short-term low-impact works in QGTTM Part 5, including:
	Workers (symbolic)
	SURVEYORS AHEAD
	LINE MARKERS AHEAD
	MOWING AHEAD or Mowing (symbolic)
	ROAD PLANT AHEAD
	• NEXT x km / NEXT 500 m
 Install or remove signs on a TGS developed by a TMD in accordance with the short-term low-impact works in QGTTM Part 5, excluding works involving: a) grading, or b) protection by a shadow vehicle with (or without) a truck-mounted attenuator, or 	Signs applicable for installation or removal by a <i>Working in Proximity to Traffic Awareness – Part 2</i> Competent Person are only those required for compliance with the relevant sections of the short-term low-impact works in QGTTM Part 5 and as listed previously.
c) the use of sections 4.1, 4.4 or 4.5.	
Select an appropriate generic TGS (from a system designed by a TMD), assess as site suitable and implement. The generic TGS must be developed in accordance with the short-term low-impact works in QGTTM	Selection and implementation of the generic TGS must be performed in accordance with the established protocol or procedure as documented by the TMD Competent Person when developing the generic TGS.
Part 5, and excludes works involving:	Signs applicable for installation or removal by a
a) grading, or	Working in Proximity to Traffic Awareness – Part 2 Competent Person are only those required for compliance with the relevant sections of the short-term low-impact works in QGTTM Part 5 and as listed previously.
 b) protection by a shadow vehicle with (or without) a truck-mounted attenuator, or 	
c) the use of sections 4.1, 4.4 or 4.5.	
Competent person – Lookout person	
Activity	Additional information
Perform lookout activity as required in the QGTTM Part 5.	Must have good eyesight, hearing and be competent to perform lookout activities.

Activity	Additional information
Drive a pilot vehicle on a worksite working with the Traffic Controllers in attendance for the purpose of traffic management at that worksite only.	Must have a current driver's licence and be competent to perform roadwork pilot vehicle driver duties.
	NOTE: This task is separate to and different from the
	requirements for pilot vehicles for heavy vehicles in
	general traffic situations.
Competent Person – Truck-mounted attenuator (TM	A) vehicle driver
Activity	Additional information
Drive a vehicle fitted with a truck-mounted attenuator (TMA) on a worksite	TMA driver must have a current and valid Heavy Vehicle drivers' licence of a suitable class to operate the TMA vehicle.
	Completed specific training and is deemed competer in the operation of a TMA.
	The TMA operator / driver must also hold the TMI competency at the appropriate road category.
Display text messages or electronic signs on VMS screens mounted on the TMA vehicle.	In accordance with requirements and instructions on the TGS.
Display of direction arrow(s) on arrow boards mounted on the TMA vehicle.	In accordance with requirements and instructions on the TGS.
Competent person – Authorised person	
Task – Install and remove	
Activity	Additional information
Install and remove advance warning signs in accordance with procedures nominated in permits; for example, 'Smoke Hazard', 'Stock'.	An example of a procedure would be Queensland Fire and Emergency Services gazette notice for cane burning.
Competent Person – Event Traffic Marshal (ETM) fo	r Special Events
(In accordance with the Traffic Marshal – Special Ex	vent Approved Procedure)
Task – Implement	
(ETMs are not to be used at roadworks or workplace	es)
Activity	Additional information
Only the signs and devices specifically nominated by the TMD on the TGS (for a permitted Special Event) as able to be installed and removed by an ETM.	Signs and devices to be installed by ETMs will be located in simple low-speed, low-risk traffic environments for the duration of a permitted Special Event.
	A TC may also install devices nominated on the TGS for an ETM.
Control traffic only at locations specifically nominated by the TMD on the TGS (for a permitted Special Event) as appropriate for an ETM.	ETMs may control traffic in low-speed, low-risk traffic environments for the duration of a permitted Special Event.
	A TC may also control traffic at a location nominated on the TGS for an ETM.

13 QGOV (13 74 68) www.tmr.qld.gov.au | www.qld.gov.au